

HyperX Cloud Headset

hyperxgaming.com

Game without pain.

Let your opponents take the blows while you game without pain. HyperX™ Cloud cradles your head in a super-soft padded headband, memory foam ear cushions and leatherette-padded cups so even your late game will be comfortable. It's affordable, so there's no pain in the price either.

Pro-gaming optimized, HyperX Cloud is HiFi capable and delivers intense audio with crystal-clear low, mid and high tones plus enhanced bass-reproduction so you can lose yourself while you win. Plus you'll look sharp while playing, thanks to the unique HyperX design.

> Memory foam ear pads

> 53mm drivers

> Interchangeable ear cups



Pro-Gaming Optimized:

- Closed cup design for enhanced passive noise cancellation
- Pure HiFi capable
- Detachable mic
- Solid aluminum build
- Braided cable
- Durable travel pouch

Features/specs on reverse >>

HYPER™
X

HyperX Cloud Headset

FEATURES/ BENEFITS

- > **Comfortable** — memory foam ear cushions with leatherette-padded headband
- > **Customizable** — switch between leatherette and velour ear cushions for varying sound profiles and feel
- > **Compatible** — with PCs, notebooks, tablets, mobile phones, airplane adapters and PS4 consoles
- > **Stylish** — now available in Mav Edition, Freestyle Series, featuring intricate, hand-drawn art with a polished gloss finish to help you stand out in the crowd
- > **Distinctive** — HyperX branded design in red and black or white and black
- > **Guaranteed** — two-year warranty, free technical support

SPECIFICATIONS

Headset

- > **Transducer type** dynamic Ø 53mm
- > **Operating principle** closed
- > **Frequency response** 15Hz–25,000 Hz
- > **Nominal impedance** 60 Ω per system
- > **Nominal SPL** 98±3dB
- > **T.H.D.** < 2%
- > **Power handling capacity** 150mW
- > **Sound coupling to the ear** circumaural
- > **Ambient noise attenuation** approx. 20 dBa
- > **Headband pressure** 5N
- > **Weight with microphone and cable** 350g
- > **Cable length and type** 1m + 2m extension + 10cm iPhone
- > **Connection** mini stereo jack plug (3.5 mm)

Microphone

- > **Transducer type** condenser (back electret)
- > **Operating principle** pressure gradient
- > **Polar pattern** cardioid
- > **Power supply** AB powering
- > **Supply voltage** 2V
- > **Current consumption** max 0.5 mA
- > **Nominal impedance** ≤2.2 kΩ
- > **Open circuit voltage** at f = 1 kHz: 20 mV / Pa
- > **Frequency response** 100–12,000 Hz
- > **THD** 2% at f = 1 kHz
- > **Max. SPL** 105dB SPL (THD≤1.0% at 1 KHz)
- > **Microphone output** -39±3dB
- > **Length mic boom** 150mm (include gooseneck)
- > **Capsule diameter** Ø6*5 mm
- > **Connection** mini stereo jack plug (3.5mm)



PART NUMBERS

Black
KHX-H3CL/WR

White
KHX-H3CLW